



# Calder Pegasus<sup>™</sup> HC EF Control Unit

The Calder Pegasus HC Electrofusion Welder gives you functionality, reliability and affordability and is capable of welding all brands of fittings up to 1000mm. Featuring a protective hard case, barcode scanning and manual data entry options, this welder is built to last.



TECHNICAL GUIDE: **TA1.5** 

## **Applications**

PE Electrofusion welding

# **Product Attributes**

Fitting size range of 20-1000mm

Barcode scanning and manual time entry

Data recording of 2000 welds

CalderSafe® Bluetooth connection

## **Approvals/Standards**

Compatible with fittings that meet AS/NZS 4129:2008

The Calder Pegasus HC is equipped with comprehensive data logging capabilities and when combined with CalderSafe® Mobile, the unit will provide you with a complete quality assurance system.

#### **Standard Features:**

- Barcode scanning and manual time entry
- Fitting size range Ø 20-1000mm
- 4m output lead
- Data recording of 2,000 welds
- Simple symbolic display
- Robust, heavy duty plastic case
- CalderSafe® Weld Data Analyser via Bluetooth connection\*
- Dual 4.0/4.7mm Cruciform Connectors

### \* Requires use of CalderSafe® App (available on Android)

| Item Code                           | EFMPEGASUS        |
|-------------------------------------|-------------------|
| Coupling Size Range                 | 20-1000mm         |
| Dimensions [HxWxL]                  | 550 x 420 x 340mm |
| Weight                              | 28kg              |
| Case Material                       | ABS Plastic       |
| Mains Input Cable Length*           | 10m               |
| Fusion Output Cable Length          | 4m                |
| Input Voltage                       | 230v              |
| Power Consumption                   | 40-60Hz           |
| Max. Input Current                  | 16A (230v)        |
| Input Power                         | 2.8kVA (230v)     |
| Output Voltage [Vac RMS]            | 8-48v             |
| Output Current [Continuous Aac RMS] | 60A               |
| Environmental Protection            | IP55              |
| Data Recording Capacity             | 2000 Records      |

Note: \* Supplied with 15 Amp male 3-pin plug.



Scan for more information

**Disclaimer**: While every effort has been made to ensure that the information in this document is correct and accurate, users of Hygrade Water product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hygrade Water unless expressly stated in any sale and purchase agreement entered into between Hygrade Water and the user. **November 2025** 

